
Dimplex®

Revillusion®

36" Built-in Electric Firebox

RBF36



Revillusion® is a completely new way of looking at fireplaces, and changing the standard for electric. A clear view through the lifelike flames, to the full brick interior, captures the charm of a wood-burning fireplace. Enjoy the look of a fireplace cut straight from the pages of a magazine by choosing Revillusion®; clearly a better fireplace.

Revillusion® by Dimplex

Revillusion®

36" Built-in Electric Firebox

RBF36



Accessories



36" Tempered Front Glass
Dimensions:
35-1/8" W x 22-1/8" H x 3/8" D
(89.1 cm x 56.1 cm x 1.1 cm)



36" Functional Doors with Tempered Glass
Dimensions:
39-3/4" W x 27-1/4" H x 1-1/4" D
(101.1cm x 69.4cm x 3.7cm)

120 V | 1,375 W | 4,400 BTU
208 V | 1,975 W | 6,745 BTU
240 V | 2,575 W | 8,794 BTU

Mood-maker Remote
Customize the light color and intensity for a fireplace that reflects your personality.



Model #	Description	Lbs / Kg	UPC	Wty*	Carton Dimensions (WxHxD)		Cube	
					Inches	cm	ft³	m³
RBF36	36" Built-in Electric Firebox	74.9 / 34.0	781052 104723	2 yrs.	41-1/4 x 15-1/4 x 31-7/8	104.6 x 38.7 x 81.0	11.6	0.3
RBFPLUG	Plug Kit	0.6 / 0.3	781052 107656	1 yr.	7 x 3 x 4	17.8 x 7.6 x 10.2	0.05	0.00
RBFGLASS36	Single Glass Pane	25.1 / 11.4	781052 108011	1 yr.	42-1/8 x 29-1/4 x 4-1/4	106.8 x 74.2 x 10.6	3.0	0.08
RBFDOOR36	36" Glass Door	32.7 / 14.7	781052 108059	1 yr.	41-7/8 x 30-1/8 x 4-5/8	106.3 x 76.4 x 11.6	3.3	0.09

Features

Revillusion® Flame Technology
Flames are larger, brighter and more random, appearing from within the logs.

Mirage™ Flame Panel
Partially frosted acrylic panel is clearly better than a mirror, showing only dazzling flames and no reflections.

ThruView™ Full-depth Design
See clear through the flames to the back of the firebox for a more authentic experience.

Mood Lighting
Customize the firebox glow with a choice of warm hues, plus midnight mode.

Color Enhancement
Adjust the flame base color to red or blue.

Realogs™ Plus
A full grate of life-size hardwood-cast logs, tiered for greater depth.

Full Brick-surround Firebox
More authentic day or night; 270-degree herringbone brick with natural soot markings.

Brightness and Flicker
Adjust light level to suit the room and choose flicker effect for enhanced firelight.

Ambient Light Sensor
Automatically adjusts firebox light to suit the room day to night.

Quick and Easy Installation
Simply frame, wire and finish – no venting, gas lines or safety screens.

Primary Heat
Option to use 240 volt supply for up to 8,800 BTU - use as part of primary heating plan; heater also operates without flame and can be deactivated.

All-season Flames
Enjoy the unique charm of a fireplace 365 days a year using the flames without the heat.

Direct-wire
Designed to be direct-wired to a 120, 208 or 240 volt circuit for a seamless look (optional plug kit available).

Low Carbon Footprint
The most sustainable fireplace option; no emissions and 100% efficient.

Specifications, finishes and dimensions are subject to change. †Limited warranty. ©2018 Glen Dimplex Americas.


SE-329-R09-122018

Revillusion®


36" Built-in Electric Firebox

RBF36


Product Dimensions:



FRONT





SIDE



TOP

Framing Dimensions:





NOTE: The materials used for the finished surround must be cut to precise dimenstions as the 1/2" (1.3 cm) self trimming flange is only to create a finished appearance.

RBF36

A	B	C	D	E	F
12-1/2" (31.8 cm)	36-5/8" (93.0 cm)	26-1/4" (66.5 cm)	60" (152.4 cm)	42-1/2" (108.0 cm)	42-1/2" (108.0 cm)